


Horizontal Cable Cross Connection (CC-X)

Section 2

Application:

CC-X Type Moulds are used for horizontal cross stranded cable connections. Cross of horizontal cables, tap cable cut cables in same plane.



Reference Code	Cable Section (mm ²)		Cartridge Size	Handle Clamp Type
	Main	Tap		
CC-X 150/50	150	50	150	NHC-80
CC-X 150/70	150	70	150	NHC-80
CC-X 150/95	150	95	200	NHC-80
CC-X 150/120	150	120	250	NHC-80
CC-X 150/150	150	150	250	NHC-80
CC-X 185/50	185	50	200	NHC-80
CC-X 185/70	185	70	200	NHC-80
CC-X 185/95	185	95	200	NHC-80
CC-X 185/120	185	120	250	NHC-80
CC-X 185/150	185	150	250	NHC-80
CC-X 185/185	185	185	300	NHC-80
CC-X 240/70	240	70	250	NHC-80
CC-X 240/95	240	95	300	NHC-80
CC-X 240/120	240	120	300	NHC-80
CC-X 240/150	240	150	400	NHC-80
CC-X 240/185	240	185	400	NHC-100
CC-X 300/70	300	70	300	NHC-80
CC-X 300/95	300	95	400	NHC-80
CC-X 300/120	300	120	400	NHC-80
CC-X 300/150	300	150	500	NHC-80
CC-X 300/185	300	185	500	NHC-100
CC-X 300/240	300	240	600	NHC-100
CC-X 300/300	300	300	600	NHC-100

Required Tools:

Suitable Mould Type: (CC-X)
Handle Clamps (NHC)
Exothermic Welding Powder
Wick Starter
Metalic Disk
Flint Ignitor

Suggested Tools:

Cleaning Tools (CTKA)
Torch Warmer (TFG)
Scraper

Titel:	Document No.:						
Horizontal Cable Cross Connection (CC-X)	Rev.:	0	Issued For Approval	97/10/20	K. J.	M.R.Hedayati	M.R.Hedayati
	Page:	1/2	Description	Date	Prepared	Checked	Approved