

ANODE TYPE	Aluminium cast anode																		
RELEVANT STANDARDS	✓IPS-M-TP-750/6 ✓ASTM B275, designation MIC (Galvomag) ✓DNV RP B401																		
SHAPE																			
Anode Dimensions	L x W x H :		mm																
WEIGHT	Net Weight:	35	Kg																
	Gross Weight:		Kg																
COMPOSITION	<table border="1"> <thead> <tr> <th>element</th> <th>composition</th> </tr> </thead> <tbody> <tr> <td>Aluminium (Al)</td> <td>reminder</td> </tr> <tr> <td>Zinc (Zn)</td> <td>2.5-5.75</td> </tr> <tr> <td>Copper (Cu)</td> <td>0.003% Max.</td> </tr> <tr> <td>Silicon (Si)</td> <td>0.12% Max.</td> </tr> <tr> <td>In</td> <td>0.015%-0.040</td> </tr> <tr> <td>Iron (Fe)</td> <td>0.09% Max.</td> </tr> <tr> <td>Cadmium (Cd)</td> <td>0.002% Max.</td> </tr> </tbody> </table>			element	composition	Aluminium (Al)	reminder	Zinc (Zn)	2.5-5.75	Copper (Cu)	0.003% Max.	Silicon (Si)	0.12% Max.	In	0.015%-0.040	Iron (Fe)	0.09% Max.	Cadmium (Cd)	0.002% Max.
element	composition																		
Aluminium (Al)	reminder																		
Zinc (Zn)	2.5-5.75																		
Copper (Cu)	0.003% Max.																		
Silicon (Si)	0.12% Max.																		
In	0.015%-0.040																		
Iron (Fe)	0.09% Max.																		
Cadmium (Cd)	0.002% Max.																		
INSPECTION AND TEST	✓Visual Inspection against any metallurgical defects ✓Anode to cable resistance test ✓weighting of anode with & without backfill																		
Electrical Specification	Utilization Factor:	85	(%)																
	Current Capacity (Min):	1500	Ahr/Kg																
	Potential: (Respect to Ag/AgCl reference electrode)	-1.05	V																